

KELLY L. ZIMMERMAN

SCOTT P. ZIMMERMAN

TITLE OF THE INVENTION

5 Methods and Systems for Communicating Vehicle Data

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation-in-part of Application No. 09/455,145, filed
December 06, 1999, and this application also claims the benefit of U.S. Provisional Application
10 No. 60/182,624, filed February 15, 2000.

BACKGROUND OF THE INVENTION

1. Field of the Invention

15 [0002] This invention generally relates to vehicles and, more particularly, to methods and
systems for acquiring and communicating vehicular data.

2. Description of the Related Art

20 [0003] Vehicle manufacturers use computers to control and to detect errors in vehicle
components. Each computer may receive data from several sensors, and the computer then uses
this data to control fans, valves, relays, and other components. When a computer receives data
that is unfamiliar or that is outside programmed limits, the computer is usually programmed to
25 send an error message. This error message is commonly displayed on the vehicle's instrument
panel as a flashing light or other indication. The driver is then alerted to return the vehicle to a
service center for repair.

[0004] Any error message or other data from the computer must currently be requested or
30 downloaded by service personnel. A service technician or engineer uses a specially programmed

device to interface with the computer. This specially programmed device is connected to the computer to read sensor data, computer data, and error codes. These specially programmed devices are expensive to purchase, and these specially programmed devices can differ between manufacturers and even between model years. Furthermore, expensive labor costs are unnecessarily required to interface with the computer and read any data or error codes. This human interaction is also prone to error. One example of these specially programmed service diagnostic tool devices is the SNAP-ON® MT2500 Scanner for on-board diagnostic evaluation (SNAP-ON® is a registered trademark of Snap-On Technologies, P.O. Box 1430, Kenosha, Wisconsin 53141-1430, www.snapon.com).

[0005] There is, accordingly, a need in the art for a method of acquiring vehicle data which is less costly, which reduces human error, and which is always cost effective to implement.

BRIEF SUMMARY OF THE INVENTION

[0006] A vehicular data acquisition and transmission device reduces the aforementioned problems. The vehicular data acquisition and transmission device includes a communication device installed within a vehicle. The vehicular data acquisition and transmission device receives vehicular data and initiates a wireless communication. This initiated wireless communication includes a representation of the vehicular data. The vehicular data may represent engine management information, powertrain management information, chassis management information, and electrical management information. The vehicular data may also include maintenance information, diagnostic error code information, odometer, fuel, or vehicle identification number (VIN) information.

[0007] Methods and systems are disclosed for communicating diagnostic messages from a vehicle. One embodiment detects the diagnostic message and initiates a wireless communication in response to the diagnostic message. The wireless communication is initiated by electronic equipment installed in the vehicle. The wireless communication represents the diagnostic message. The wireless communication could also represent a vehicle identification number or

the vehicle's location. The wireless communication is initiated to a manufacturer, a customer service center, or a dealership. Another embodiment detects the diagnostic message and requests to initiate a wireless communication in response to the diagnostic message. If the request is approved, electronic equipment installed in the vehicle initiates the wireless communication.

5

[0008] Methods are also disclosed for returning a rental vehicle to a rental agency facility. One method detects the location of the rental vehicle and initiates a wireless communication representing rental agency information. The wireless communication is initiated by electronic equipment installed in the rental vehicle. The wireless communication represents at least one of
10 mileage, fuel, and a number identifying the rental vehicle. Another method detects the location of the rental vehicle and wirelessly communicates a request to electronic equipment installed in the rental vehicle. The request represents a request for rental agency information. If the request is approved, electronic equipment installed in the rental vehicle initiate a wireless communication representing the requested rental agency information.

15

[0009] A vehicle is also disclosed. The vehicle has a powertrain system driving at least one wheel and tire assembly. At least one powertrain sensor monitors the powertrain system, with the at least one powertrain sensor producing a powertrain sensor signal. A processor receives the powertrain sensor signal, and the processor generates a powertrain system diagnostic message at
20 predetermined values of the powertrain sensor signal. A wireless communication device installed in the vehicle initiates a wireless communication in response to the powertrain system diagnostic message, with the wireless communication representing the powertrain system diagnostic message.

25

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0010] These and other features, aspects, and advantages of the present invention will be better understood when the following Detailed Description of the Invention is read with reference to the accompanying drawings, wherein:

30

FIG. 1 is a schematic of a vehicle incorporating a vehicular data acquisition and transmission device;

FIG. 2 is a schematic of the vehicular data acquisition and transmission device;

FIG. 3 is a schematic of a system for wireless acquiring vehicular data;

FIG. 4 is an alternative schematic of the vehicular data acquisition and transmission device;

FIG. 5 is also an alternative schematic of the vehicular data acquisition and transmission device;

FIG. 6 is a flowchart showing a method of communicating diagnostic messages from a vehicle; and

FIG. 7 is a flowchart showing a method of returning a rental vehicle to a rental agency facility.

DETAILED DESCRIPTION OF THE INVENTION

[0011] FIG. 1 is a schematic of a vehicle 20 incorporating a vehicular data acquisition and communication device 22. The vehicle includes at least one wheel and tire assembly 24, and at least one powertrain system 26 driving the at least one wheel and tire assembly 24. The vehicular data acquisition and communication device 22 includes a communication device 28. The communication device 28 communicates vehicular data. The communication device 28 receives vehicular data and initiates a communication representing or including the vehicular data. The vehicular data may include engine or powertrain management system information 30 from an engine, electric motor, or transmission system of the vehicle. The vehicular data may also include electrical management system information 32 from an electrical system of the vehicle or chassis management system information 34 from a chassis system of the vehicle.

[0012] The engine or powertrain management system information 30 includes information used to control engine and transmission performance. Many automotive manufacturers use one or more computers to control performance of an automobile's engine, transmission, and other powertrain components. (An Electronic Control Module, or "ECM," is one example of an on-

board computer used to control vehicular powertrains.) Sensors, switches, and actuators provide data to these computers, and these computers use this data to control emissions devices, cooling fans, ignition, air/fuel ratios, and many other performance variables. The communication device 28 can be used to communicate the information detected by these sensors, switches, and actuators.

[0013] The vehicular data acquisition and communication device 22 initiates a communication. The vehicular data acquisition and communication device 22 automatically communicates engine or powertrain management system information 30. The vehicular data acquisition and communication device 22 need not be prompted or commanded to communicate the engine or powertrain management system information 30. The vehicular data acquisition and communication device 22 automatically communicates the engine or powertrain management system information 30, independently of a service diagnostic tool or human intervention. The vehicular data acquisition and communication device 22 can initiate a communication whenever a predetermined event occurs. The vehicular data acquisition and communication device 22, for example, can initiate a communication any time a diagnostic error code is detected. The vehicular data acquisition and communication device 22 could also initiate a communication at certain time intervals, mileage intervals, or any other interval or combination of intervals.

[0014] "Vehicular data," as used herein, can be any signals or information used by the engine or powertrain management system. Vehicular data may include any of the sensor, switch, or actuator data collected by the engine or powertrain management system. Those skilled in the art recognize there are many sensors, switches, and actuators used in automobiles, and the number of sensors, switches, and actuators grows each model year. The vehicular data may include, for example, air intake temperature sensors, engine coolant sensors, throttle position sensors, manifold air pressure sensors, oxygen sensors, mass air flow sensors, ignition sensors, knock sensor, EGR sensors, and many other sensors.

[0015] "Vehicular data" may also include any diagnostic error codes flagged by the engine or powertrain management system. Sensors, switches, and actuators, as mentioned above, provide

data to one or more on-board computers. These computers use this data to control emissions devices, cooling fans, ignition, air/fuel ratios, and many other components and performance variables. When these computers detect sensor inputs, or other inputs, that are outside of programmed limits, the computer often sets a diagnostic error code. The communication device
5 28 can be used to initiate a communication representing or containing this diagnostic error code.

[0016] The communication device 28 could initiate a wireless communication. Wirelessly transmitting engine or powertrain management system information 30 is greatly advantageous for vehicular service efforts. The vehicle's engine or powertrain management system
10 information 30 could be automatically communicated to a dealership or manufacturer service center. The dealership or manufacturer service center would immediately be informed of any diagnostic error codes set by the engine or powertrain management system. Because the vehicular data acquisition and communication device 22 could also transmit a Vehicle Identification Number (VIN), the dealership or manufacturer service center would also know the
15 customer name and any customer profile. The dealership or manufacturer service center could immediately determine the repair procedure for the diagnostic error code, and the dealership could immediately determine the availability of repair parts. If a repair part(s) is available, the dealership could contact the customer and make a service appointment. If a repair part(s) are not available, the dealership could automatically order the repair part and still contact the customer
20 and make a service appointment.

[0017] Because the vehicular data acquisition and communication device 22 informs the dealership of engine or powertrain management system information 30, the dealership could even send a mobile repair team to the customer's home or work. If the vehicular data acquisition
25 and communication device 22 also communicates the Vehicle Identification Number (VIN), the customer profile could inform the dealership of the customer's home address or work address. Thus, the vehicular data acquisition and communication device 22 could allow the dealership to repair the vehicle without the customer traveling to the dealership. The customer profile could be configured to show the customer's desired service hours, special needs, or any other
30 information.

037618 "220004
[0018] Wirelessly transmitting engine or powertrain management system information 30 is greatly advantageous for engineering development efforts. Because the vehicular data acquisition and communication device 22 initiates a communication representing engine or powertrain management system information 30, the vehicle manufacturer's engineering and warranty teams could be immediately informed of component or system quality issues. Wirelessly transmitting engine or powertrain management system information 30, for example, allows the engineering and warranty teams to quickly determine the root cause(s) of any errors detected by the engine or powertrain management system. The engineering and warranty teams can immediately begin formulating warranty and quality plans to eliminate the error. The vehicular data acquisition and communication device 22 allows manufacturers to very quickly respond to warranty and quality issues. Because vehicle manufacturers are quickly alerted to warranty and quality issues, the vehicular data acquisition and communication device 22 could greatly reduce the number of defective vehicles manufactured and the number of defective vehicles shipped to dealers.

[0019] As FIG. 1 shows, the vehicular data acquisition and communication device 22 could also communicate electrical management system information 32. The electrical management system information 32 includes information used to control the vehicle's electrical system. Many automotive manufacturers use one or more computers to control the vehicle's electrical system. Sensors, switches, and actuators provide data to these computers, and these computers use this data to detect under and over voltage or current conditions, open circuit conditions, circuit failures, power failures, battery failures, and many other electrical system concerns. The communication device 28 can be used to initiate a communication representing the condition of the vehicle electrical system.

[0020] As FIG. 1 also shows, the vehicular data acquisition and communication device 22 could also communicate chassis management system information 34. Today's vehicles are increasingly using one or more computers to control advanced chassis/suspension components. Hydraulic and/or pneumatic leveling systems, adaptive/active suspension systems, magneto-

5 rheological suspension components, electric steering systems, and four wheel steering systems are just a few of the technological advances in chassis design. These chassis advances use one or more computers to control these systems. Steering wheel angle sensors, yaw, pitch, and roll accelerometer sensors, height sensors, shock absorber valving sensors, and many other chassis sensors, switches, and actuators are used to detect the state of the chassis system. The communication device 28 can be used to communicate the condition of the vehicle chassis system.

10 [0021] “Vehicular data,” as used herein, may also include any information used by the electrical management system and the chassis management system. Vehicular data may include any of the sensor, switch, or actuator data collected by the electrical management system and the chassis management system. Sensor data, switch data, actuator data, and even error codes can be wirelessly communicated by the vehicular data acquisition and communication device 22. Even maintenance schedules could be communicated so that dealers could automatically schedule and perform maintenance procedures.

15 [0022] There are many advantages of wirelessly communicating electrical management system information 32 and the chassis management system information 34. Dealership service groups, like a vehicle manufacturer’s warranty and engineering teams, can quickly learn of vehicle quality or maintenance concerns. Dealers and manufacturers can quickly respond and formulate action plans. Because vehicle manufacturers and dealers are quickly alerted to warranty and quality issues, the vehicular data acquisition and communication device 22 could greatly reduce the number of defective vehicles manufactured and the number of defective vehicles shipped to dealers.

25 [0023] FIG. 2 is a schematic of the vehicular data acquisition and communication device 22. The communication device 28 receives engine or powertrain management system information 30, electrical management system information 32, and chassis management system information 34. FIG. 2 shows the communication device may have power inputs 36 and 38, and the communication device may include an antenna 40. The communication device 28 can be any

means for communicating the vehicular data. As those skilled in the art recognize, the communication device 28 may be a cellular phone device, a paging device, or a satellite communication device. The communication device 28 may operate on any frequency or any portion of the electromagnetic spectrum (e.g., RF, infrared). The communication device 28 may also be analog or digital.

[0024] FIG. 3 is a schematic of a system 42 for wirelessly acquiring vehicular data. The system 42 includes the vehicular data acquisition and communication device 22. The communication device 28 receives the vehicular data and wirelessly transmits the vehicular data. At least one other communication device 44 wirelessly receives the vehicular data from the communication device 28. The at least one other communication device 44 may also have an antenna 46, and the vehicular data is communicated from the at least one other communication device 44 to one or more data acquisition devices 48. Those skilled in the art recognize the one or more data acquisition devices 48 can be a personal computer, laptop computer, or any other data storage device.

[0025] FIG. 3 also shows a method of communicating the vehicular data. The method includes initiating a communication representing the vehicular data. The method could include initiating a wireless communication of the vehicular data from the vehicle to a dealership. The method may include initiating a communication of the vehicular data from the dealership to a manufacturer. The method could include initiating a communication of the vehicular data over the Internet from the dealership to the manufacturer. The method additionally could include initiating a wireless communication of the vehicular data from the dealership to a manufacturer or from the vehicle to a manufacturer. The method alternatively could include initiating a wireless communication of the vehicular data from the vehicle to a rental agency.

[0026] FIG. 4 is an alternative schematic of the vehicular data acquisition and communication device 22. FIG. 4 shows the communication device 28 receiving vehicle management system information 50. FIG. 4 acknowledges that the separate computers shown in FIGS. 1 and 2, and used to control the engine or powertrain management system, the electrical management system,

and the chassis management system, may be combined into one vehicle management system. This vehicle management system would reduce vehicle component costs by having a single computer or controller control all subsystems of the vehicle. Thus, the communication device 28 would receive vehicle management system information 50 from a single vehicle computer.

5

[0027] Those skilled in the art also recognize the vehicular data acquisition and communication device 22 could receive direct inputs from any management system. As FIG. 4 suggests, any engine, powertrain, electrical, or chassis management system used in a vehicle could send direct inputs to the vehicular data acquisition and communication device 22. A wiring harness or cable could plug from any computer or controller in the vehicle to the communication device 28. This type of connectivity would eliminate translators or other software measures between each computer and the vehicular data acquisition and communication device 22.

10

[0028] FIG. 5 is also an alternative schematic of the vehicular data acquisition and communication device 22. FIG. 5 shows the vehicular data acquisition and communication device 22 specially configured for rental operations. The communication device 28 could receive vehicular data such as Vehicle Identification Number (VIN) 52, fuel level 54, and odometer 56. The vehicular data acquisition and communication device 22 shown in FIG. 5 would allow all rental customers to simply park the vehicle at the rental agency and immediately proceed to an airline gate or other destination. The rental agency would immediately know the VIN, the fuel level, and the odometer. The vehicular data acquisition and communication device 22 greatly speeds the return of rental vehicles and promotes further rental customer satisfaction. Because the vehicular data acquisition and communication device 22 communicates VIN, fuel, and mileage, the rental agency can also reduce labor costs from the rental return procedure.

15

20

25

[0029] Rental agencies could still provide the customer with a receipt of the rental transaction. Although the vehicular data acquisition and communication device 22 eliminates the customer from having to log and/or report fuel and mileage, the customer may still need a receipt of the rental transaction. The vehicular data acquisition and communication device 22, for example, would allow the rental agency to print a receipt on a bus or other rental agency ground

30

transportation. The customer could simply return the vehicle, immediately walk to the rental agency bus, and a printed receipt would be available from the driver or from a terminal in the bus. The agency could, of course, email a receipt to the rental customer.

5 [0030] Other features of the vehicular data acquisition and communication device 22 are security and convenience. The vehicular data acquisition and communication device 22 could be designed to only transmit vehicular data when prompted. This feature would save power and would also prevent personal data from unnecessary transmission. A rental agency or dealer, for example, could “ping” or prompt the vehicular data acquisition and communication device 22
10 when the vehicle is within range. The vehicular data acquisition and communication device 22 would then communicate the vehicular data. The vehicular data acquisition and communication device 22 could also be prompted for vehicular data (such as VIN) when the vehicle has been stolen. Triangulation, GPS, or other methods could be used to pinpoint the location of a stolen vehicle communicating vehicular data. The vehicular data acquisition and communication
15 device 22 could also be used to facilitate electronic commerce. The vehicular data acquisition and communication device 22 could transmit credit card information to a local gas station or other vendor. When the gas station or vendor prompts the vehicular data acquisition and communication device 22, an e-commerce payment would be electronically made. Likewise, the vehicular data acquisition and communication device 22 could initiate an emergency
20 communication (such as dialing 911) at a predetermined sensor value. For example, an accelerometer value representing a collision could cause the vehicular data acquisition and communication device 22 to initiate a communication to police, to emergency crews, to family or friends, or any other entity. Triangulation, GPS, or other methods could be used to pinpoint the location of the vehicle initiating the communication. The vehicular data acquisition and
25 communication device 22 could also contact a fuel delivery company when fuel is low. The vehicular data acquisition and communication device 22 could be instructed to initiate a wireless communication to a fuel delivery company. Fuel could be delivered to a requested location or a preferred location (such as work) at a certain time.

FIG. 6 is a flowchart showing a method of communicating diagnostic messages from a vehicle. The diagnostic message is detected (Block 58) and stored (Block 60). A request is made to initiate a wireless communication in response to the diagnostic message (Block 62). If the request is not approved, then the request is delayed (Block 64). If the request is approved, electronic equipment installed in the vehicle initiate the wireless communication (Block 66). The wireless communication may represent the diagnostic message, the vehicle's identification number, and/or the vehicle's location (Block 68). The wireless communication may be received at a dealership, vehicle manufacturer, vehicle service center, customer service center, or rental agency (Block 70). A service appointment could then be scheduled (Block 72). An occupant of the vehicle could be notified that the diagnostic message has been communicated (Block 74). The occupant could be notified by a lighted indication on an instrument panel, by recorded or programmed voice, by email, by page, by telephone, or any other means. If the diagnostic message is simple to resolve, instructions could be communicated to the occupant to resolve the diagnostic message.

FIG. 7 is a flowchart showing a method of returning a rental vehicle to a rental agency facility. The location of the rental vehicle is detected by triangulation or by GPS (Block 76). Once the rental vehicle is known to be proximate to the rental agency facility, or within the rental agency facility, the rental agency wirelessly communicates a request for electronic equipment to communicate rental agency information (Block 78). Electronic equipment installed within the rental vehicle, alternatively, could initiate the wireless communication representing rental agency information (Block 80). The rental agency information represents VIN, fuel, mileage, and any other desired information (Block 82).

Although FIG. 1 shows an automobile, those skilled in the art recognize the vehicular data acquisition and communication device 22 is certainly applicable to other vehicular transportation platforms. Light, medium, and heavy-duty trucks, for example, may also utilize the vehicular data acquisition and communication device 22 to communicate vehicular data. Boats, ships, and aircraft may also utilize the vehicular data acquisition and communication device 22 to communicate vehicular data. The vehicular data acquisition and communication

device 22 is also applicable to hybrid-electric vehicles and electric vehicles. Even generators, lawn equipment, electric golf carts, and any other platform using a combustion engine(s) or electric motor(s) can utilize the vehicular data acquisition and communication device 22 to communicate the vehicular data.

5

[0034] While the present invention has been described with respect to various features, aspects, and embodiments, those skilled and unskilled in the art will recognize the invention is not so limited. Other variations, modifications, and alternative embodiments may be made without departing from the spirit and scope of the present invention.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000